

Sublimation Printer | S161&S1612

Features 特点



Different Printhead Available

Epson DX5,XP600, i3200 printheads available. Meet the requirement of different clients.



Integrated Temperature Control

Control the front, middle and rear heater in one place. Integrated heater controller have less fault than separate ones.



Heating and Drying System

Front and middle and rear heating system, frond drying fan are standard equipped to help dry the printed material fast.



Branded parts

Greatly increased the lifetime and stability of the machine. For example, Hiwin guide rail, German Igus drag chain, Italian Megadyne belt.



ink station

Automatic up&down ink station, automatic cleaning closed heads nozzles, so that the heads nozzles are always in good condition.





Specification 参数

ModelNO.		S161	S1612	S181	S1812
Printhead		1/2EpsonXP600/DX5/I3200heads			
Resolution(dpi)		1440dpi	2880dpi	1440dpi	2880dpi
Media	Width	1.6m 1.8m		m	
	Types	Sublimation paper			
Speed	4 pass	20sqm/h	25sqm/h	20sqm/h	30sqm/h
	6 pass	15sqm/h	19sqm/h	15sqm/h	22sqm/h
	8 pass	10sqm/h	14sqm/h	10sqm/h	15sqm/h
InkColor		СМҮК			
InkType		SublimationInk			
InkDroplet		1.5-21 plVariable			
Cleaning		AutomaticCleaning,Anti- CloggingFlashFunction&CappingSystem			
Feed&TakeUp		AutomaticMediaFeeding(Standard)&TakeUpSystem(Optional)			
Environment		Temperature:20-28°C,Humidity:40-60%			
RipSoftware		Maintop(Standard)/PhotoPrint(Optional)			
Interface		USB3.0			
Power		Machine50/60HZ,110/220V,1200W			
PackingSize&Weight		2700x750x75	2950x750x75	2950x750x750mm/190KG	