



Eco Solvent Printer

2.5/3.2m , Epson DX5/XP600/I3200 Printhead

- Dual Heads
- 4/6 Color
- Variable Dot
- 3-Stage Heater



Eco Solvent Printer | W2512&W3212

● Features




Different Printhead Available

Epson DX5, XP600, i3200 printheads available. Meet the requirement of different clients.



Big Functional Control Panel

Adopts the latest program Intelligent Error Auto-Detection boards, it can guide user to find solution very quickly.



Anti-collision Function

Anti-collision system is equipped to protect the printhead and carriage all the time.



High Quality Branded Guide Rail

Equipped Epson XP600/DX5/I3200 Head.



Large capacity ink supply

Intelligent ink supply system, constant liquid level, to ensure high speed and high output of printing ink, capacity up to 2000ml.

- ★ Control the front, middle and rear heater in one place. Integrated heater controller have less fault than separate ones.
- ★ Wide pinch roller keeps smooth movement of the media. And it has proper pressure to ensure accurate media step while not make any footprint of the pinch roller.
- ★ IGUS drag chain itself is a guarantee of quality, takes the printer stability to a new level. Effectively protect ink tube and cables
- ★ Automatic up&down ink station, automatic cleaning closed heads nozzles, so that the heads nozzles are always in good condition.



● Specification

Model NO.	W2512	W3212	
Printhead	2 Epson XP600/DX5/I3200 heads		
Resolution(dpi)	2880dpi		
Media	Width	2.5m	3.2m
	Types	Flex Banner, Vinyl, One Way Vision, Banner Cloth, Window Film, Mesh...	
Speed	4 pass	40 sqm/h	45 sqm/h
	6 pass	20 sqm/h	25 sqm/h
	8 pass	15 sqm/h	18 sqm/h
Ink Color	CMYK	CMYK	
Ink Type	Eco Solvent Ink		
Ink Droplet	1.5-21pl Variable		
Cleaning	Automatic Cleaning, Anti-Clogging Flash Function & Capping System		
Feed & Take Up	Automatic Media Feeding (Standard) & Take Up System (Optional)		
Environment	Temperature: 20-28°C, Humidity: 40-60%		
Rip Software	Maintop (Standard) / PhotoPrint (Optional)		
Interface	USB3.0		
Power	Machine 50/60HZ, 110/220V, 2500W		
Packing size/weight	3820x740x760mm/400kg	4420x740x760mm/450kg	

Specifications are subject to change without notice.